



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/475,452	12/30/1999	ANAND MURTHY	042390.P7794	6341

7590 12/14/2006

MICHAEL A BERNADICOU  
BLAKELY SOKOLOFF TAYLOR & ZAFMAN LLP  
12400 WILSHIRE BOULEVARD  
7TH FLOOR  
LOS ANGELES, CA 90025

EXAMINER

LEE, EUGENE

ART UNIT	PAPER NUMBER
----------	--------------

2815

DATE MAILED: 12/14/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

## Office Action Summary

Application No.

09/475,452

Applicant(s)

MURTHY ET AL.

Examiner

Eugene Lee

Art Unit

2815

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 20 November 2006.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-6,8,9 and 11-15 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-6,8,9,11-15 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |  |   |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## DETAILED ACTION

### *Claim Rejections - 35 USC § 112*

1. The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

2. Claims 1 thru 6, 8, 9, and 11 thru 15 rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention.

The specification does not disclose the source/drain regions having a second inwardly concaved geometry with second inflection points.

For example, in FIG. 2, it appears there is only one inwardly concaved geometry wherein the one inflection point 260 occurs. However, there does not appear to be any other areas that could be called an inwardly concaved geometry or have an inflection point.

### *Claim Rejections - 35 USC § 103*

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Art Unit: 2815

4. In view of the 112 rejection, claims 1, 8, 9, and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi 5,060,033. Takeuchi discloses (see, for example, Fig. 1h) a MOS transistor (device) comprising an insulating film (gate dielectric) 103, substrate (substrate that has a first conductivity region) 101, gate electrode 105, side wall insulating film (pair of sidewall spacers) 108, and source and drain regions (a pair of silicon or silicon alloy inwardly concaved source/drain region of a second conductivity type formed in said substrate) 106. The source and drain regions are inwardly concaved and bend (inflection points) directly underneath the gate electrode. The channel region (first channel region) directly beneath the gate electrode is larger than the channel region (second channel region) between the inflection points.

Takeuchi does not disclose an inflection point which occurs between 50-250 Å laterally beneath said gate electrode and at a depth of between 25-100 Å beneath said gate dielectric. However, the depth of the source/drain junctions and the distance between the inflection point and the gate electrode and gate dielectric are result effective variables that one of ordinary skill in the art would optimize for affecting the channel region in a field effect transistor. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention was made to have an inflection point which occurs between 50-250 Å laterally beneath said gate electrode and at a depth of between 25-100 Å beneath said gate dielectric, in order to form a channel region, and since it has been held that discovering the optimum value of a result effective variable involves only routine skill in the art. In re Boesch, 617 F. 2d 272, 205 USPQ 215 (CCPA 1980).

Regarding the limitation "having a concentration of impurities in a range between  $1 \times 10^{18} / \text{cm}^3 - 3 \times 10^{21} / \text{cm}^3$ ", see, for example, column 4, lines 66-67 wherein Takeuchi discloses a range between  $1 \times 10^{16} \text{ cm}^{-3}$  to  $6 \times 10^{18} \text{ cm}^{-3}$ .

Art Unit: 2815

Regarding the limitation “recesses, wherein the recesses have an inwardly concaved geometry with inflection points; ... a silicon or silicon alloy layer deposited into the recesses”, this is a product-by-process limitation of forming the source/drain regions, and since the claims are directed towards structure, and Takeuchi structurally discloses source/drain regions, the claims are not structurally distinct from that what is shown in Takeuchi.

Regarding claims 8, and 9, see, for example, column 8, lines 18-21 wherein Takeuchi discloses an n-channel transistor as well as a p-channel transistor.

5. Claim 2 is rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi ‘033 as applied to claims 1, 8, 9, and 11 above, and further in view of Takeuchi 5,970,351. Takeuchi ‘033 does not disclose the source/drain regions extending above the gate dielectric and wherein the top surface of said silicon or silicon alloy is spaced further from said gate electrode than the silicon or silicon alloy adjacent to said gate dielectric. However, Takeuchi ‘351 discloses (see, for example, FIG. 11 (c)) a MOSFET comprising elevated source and drain regions 7B with a facet structure. In column 12, lines 45-63, Takeuchi ‘351 teaches that such a structure provides reduced parasitic capacitance. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to have the source/drain regions extending above the gate dielectric and wherein the top surface of said silicon or silicon alloy is spaced further from said gate electrode than the silicon or silicon alloy adjacent to said gate dielectric in order to reduce parasitic capacitance.

Art Unit: 2815

6. Claim 3 is rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi '033 as applied to claims 1, 8, 9, and 11 above, and further in view of Choi 6,057,582. Takeuchi does not disclose a gate dielectric layer being thicker beneath the outside edge of said gate electrode than the gate dielectric layer beneath the center of said gate electrode. However, Choi discloses (see, for example, FIG. 2) a semiconductor device comprising a gate insulating film with both sides thicker than a thickness in the center. Choi teaches (see, for example, abstract) that such a gate insulating film reduces hot carrier effects. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to have a gate dielectric layer being thicker beneath the outside edge of said gate electrode than the gate dielectric layer beneath the center of said gate electrode in order to reduce hot carrier effects.

7. Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi '033 in view of Takeuchi '351 as applied to claim 2 above, and further in view of Choi 6,057,582. Takeuchi '033 in view of Takeuchi '351 does not disclose a gate dielectric layer being thicker beneath the outside edge of said gate electrode than the gate dielectric layer beneath the center of said gate electrode. However, Choi discloses (see, for example, FIG. 2) a semiconductor device comprising a gate insulating film with both sides thicker than a thickness in the center. Choi teaches (see, for example, abstract) that such a gate insulating film reduces hot carrier effects. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to have a gate dielectric layer being thicker beneath the outside edge of said gate electrode than the gate dielectric layer beneath the center of said gate electrode in order to reduce hot carrier effects.

Art Unit: 2815

8. Claims 5 and 6 are rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi '033 as applied to claims 1, 8, 9, and 11 above, and further in view of Choi et al. 5,793,088. Takeuchi does not disclose a pair of deposited silicon or silicon alloy regions having a first conductivity type formed between said pair of deposited silicon or silicon alloy source/drain regions of said second conductivity type and said first conductivity type region. However, Choi discloses (see, for example, FIG. 2 and FIG. 3) a structure 106 comprising halo regions 120, 122. Choi teaches that halo regions provide higher punchthrough voltage. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to use halo regions in order to attain a higher punchthrough voltage.

9. Claim 12 is rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi '033 as applied to claims 1, 8, 9, and 11 above, and further in view of Hwang 5,567,966. Takeuchi does not disclose a silicide formed on said silicon or silicon alloy source/drain regions. However, Hwang discloses (see, for example, Fig. 6) a transistor comprising source and drain regions 24, and  $\text{TiSi}_2$  regions (silicide) 20. In column 2, lines 17-19, Hwang teaches reduced source/drain resistance. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to have a silicide formed on said silicon or silicon alloy source/drain regions in order to reduce resistance.

10. Claim 13 is rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi '033 in view of Wieczorek et al. 6,274,894 B1 in view of Takeuchi 5,970,351. Takeuchi '033 discloses (see, for example, Fig. 1h) a MOS transistor (device) comprising an insulating film (gate

Art Unit: 2815

dielectric) 103, substrate (first conductivity region of a substrate) 101, gate electrode 105, side wall insulating film (pair of sidewall spacers) 108, and source and drain regions (a pair of silicon or silicon alloy inwardly concaved source/drain region of a second conductivity type formed in said substrate) 106. The source and drain regions are inwardly concaved and bend (inflection points) directly underneath the gate electrode. The channel region directly beneath the gate electrode is larger than the channel region between the inflection points. Takeuchi '033 does not disclose silicon-germanium alloy source/drain regions. However, Wieczorek discloses (see, for example, column 6, lines 8-23) that SiGe (silicon-germanium) in the source/drain regions have a lower bandgap, which lowers contact resistance. Therefore it would have been obvious to one of ordinary skill in the art at the time of invention to use silicon-germanium alloy in order to lower contact resistance.

Takeuchi '033 in view of Wieczorek does not disclose the source/drain regions extending above the gate dielectric and wherein the top surface of said silicon or silicon alloy is spaced further from said gate electrode than the silicon or silicon alloy adjacent to said gate dielectric. However, Takeuchi '351 discloses (see, for example, FIG. 11 (c)) a MOSFET comprising elevated source and drain regions 7B with a facet structure. In column 12, lines 45-63, Takeuchi '351 teaches that such a structure provides reduced parasitic capacitance. Therefore, it would have been obvious to one of ordinary skill in the art at the time of invention to have the source/drain regions extending above the gate dielectric and wherein the top surface of said silicon or silicon alloy is spaced further from said gate electrode than the silicon or silicon alloy adjacent to said gate dielectric in order to reduce parasitic capacitance.



Art Unit: 2815

Regarding the limitation “recesses, ... wherein the recesses have an inwardly concaved geometry with inflection points; a silicon-germanium alloy layer deposited into the recesses”, this is a product-by-process limitation that discloses a method of forming source/drain regions that are inwardly concave, however, since the claims are directed towards product, such process claims, which do not structurally distinguish the product, are given no patentable weight.

11. Claim 14 is rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi 5,060,033 in view of Wieczorek et al. '894 B1 in view of Takeuchi '351 as applied to claim 13 above, and further in view of Choi 6,057,582. Takeuchi '033 in view of Wieczorek in view of Takeuchi '351 does not disclose a gate dielectric layer being thicker beneath the outside edges of said gate electrode than the gate dielectric layer beneath the center of said gate electrode. However, Choi discloses (see, for example, FIG. 2) a semiconductor device comprising a gate insulating film with both sides thicker than a thickness in the center. Choi teaches (see, for example, abstract) that such a gate insulating film reduces hot carrier effects. Therefore it would have been obvious to one of ordinary skill in the art at the time of invention to have a gate dielectric layer being thicker beneath the outside edges of said gate electrode than the gate dielectric layer beneath the center of said gate electrode in order to reduce hot carrier effects.

12. Claim 15 is rejected under 35 U.S.C. 103(a) as being unpatentable over Takeuchi 5,060,033 in view of Wieczorek et al. 6,274,894 B1. Takeuchi discloses (see, for example, ig. 1h) a MOS transistor (device) comprising an insulating film (gate dielectric) 103, substrate (first conductivity region of a substrate) 101, gate electrode 105, side wall insulating film (pair of

Art Unit: 2815

sidewall spacers) 108, and source and drain regions (a pair of silicon or silicon alloy inwardly concaved source/drain region of a second conductivity type formed in said substrate) 106. The source and drain regions are inwardly concaved and bend (inflection points) directly underneath the gate electrode. The channel region (first channel region) directly beneath the gate electrode is larger than the channel region (second channel region) between the inflection points. Takeuchi does not disclose silicon-germanium alloy source/drain regions. However, Wieczorek discloses (see, for example, column 6, lines 8-23) that SiGe (silicon-germanium) in the source/drain regions have a lower bandgap, which lowers contact resistance. Therefore it would have been obvious to one of ordinary skill in the art at the time of invention to use silicon-germanium alloy in order to lower contact resistance.

Regarding the limitation "recesses, wherein the recesses have an inwardly concaved geometry with inflection point; a silicon-germanium alloy layer deposited into the recesses", this is a product-by-process limitation that discloses a method of forming source/drain regions that are inwardly concave, however, since the claims are directed towards product, such process claims, which do not structurally distinguish the product, are given no patentable weight.

### ***OPTIMIZATION OF RANGES***

#### **A. Optimization Within Prior Art Conditions or Through Routine Experimentation**

Generally, differences in concentration or temperature will not support the patentability of subject matter encompassed by the prior art unless there is evidence indicating such concentration or temperature is critical. "[W]here the general conditions of a claim are disclosed in the prior art, it is not inventive to discover the optimum or workable ranges by routine

Art Unit: 2815

experimentation." In re Aller, 220 F.2d 454, 456, 105 USPQ 233, 235 (CCPA 1955) (Claimed process which was performed at a temperature between 40°C and 80°C and an acid concentration between 25% and 70% was held to be prima facie obvious over a reference process which differed from the claims only in that the reference process was performed at a temperature of 100°C and an acid concentration of 10%.); >see also Peterson, 315 F.3d at 1330, 65 USPQ2d at 1382 ("The normal desire of scientists or artisans to improve upon what is already generally known provides the motivation to determine where in a disclosed set of percentage ranges is the optimum combination of percentages.");< \*\* In re Hoeschele, 406 F.2d 1403, 160 USPQ 809 (CCPA 1969) (Claimed elastomeric polyurethanes which fell within the broad scope of the references were held to be unpatentable thereover because, among other reasons, there was no evidence of the criticality of the claimed ranges of molecular weight or molar proportions.). For more recent cases applying this principle, see Merck & Co. Inc. v. Biocraft Laboratories Inc., 874 F.2d 804, 10 USPQ2d 1843 (Fed. Cir.), cert. denied, 493 U.S. 975 (1989); In re Kulling, 897 F.2d 1147, 14 USPQ2d 1056 (Fed. Cir. 1990); and In re Geisler, 116 F.3d 1465, 43 USPQ2d 1362 (Fed. Cir. 1997).

**B. Only Result-Effective Variables Can Be Optimized**

A particular parameter must first be recognized as a result-effective variable, i.e., a variable which achieves a recognized result, before the determination of the optimum or workable ranges of said variable might be characterized as routine experimentation. In re Antonie, 559 F.2d 618, 195 USPQ 6 (CCPA 1977) (The claimed wastewater treatment device had a tank volume to contractor area of 0.12 gal./sq. ft. The prior art did not recognize that treatment capacity is a function of the tank volume to contractor ratio, and therefore the parameter optimized was not

Art Unit: 2815

recognized in the art to be a result-effective variable.). See also *In re Boesch*, 617 F.2d 272, 205 USPQ 215 (CCPA 1980) (prior art suggested proportional balancing to achieve desired results in the formation of an alloy).

### **Product-by-Process Limitations**

While not objectionable, the Office reminds Applicant that “product by process” limitations in claims drawn to structure are directed to the product, per se, no matter how actually made. *In re Hirao*, 190 USPQ 15 at 17 (footnote 3). See also, *In re Brown*, 173 USPQ 685; *In re Luck*, 177 USPQ 523; *In re Fessmann*, 180 USPQ 324; *In re Avery*, 186 USPQ 161; *In re Wethheim*, 191 USPQ 90 (209 USPQ 554 does not deal with this issue); *In re Marosi et al.*, 218 USPQ 289; and particularly *In re Thorpe*, 227 USPQ 964, all of which make it clear that it is the patentability of the final product per se which must be determined in a “product by process” claim, and not the patentability of the process, and that an old or obvious product produced by a new method is not patentable as a product, whether claimed in “product by process” claims or *otherwise*. Note that applicant has the burden of proof in such cases, as the above case law makes clear. Thus, no patentable weight will be given to those process steps which do not add structural limitations to the final product.

### ***Response to Arguments***

13. Applicant's arguments filed 6/12/06 have been fully considered but they are not persuasive.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Kenneth Parker can be reached on 571-272-2298. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2815

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Eugene Lee  
August 14, 2006

**EUGENE LEE**  
**PRIMARY EXAMINER**

A handwritten signature in black ink, consisting of a stylized 'E' followed by a large, sweeping loop.